

INTERFACCE E DIMENSIONI ESTERNE:	SN:	905472
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE					
richiesta			misurata		richiesta			misurata		richiesta			misurata		
			E1308												
	Y2	M6x12	Pg	M6x12		L1	60	Cr	60						
Ø	S2	165 ^{+0,1 -0,1}	Cr	165		L2	60	Cr	60		Ø	B	181 ^{+0,05 +0,025}	µm	181
	A	332	µm	332,7		J	130	Cr	130		Ø	C	38	µm	38,05
	E	240	Cr	240		K	11	Cr	11			D	8	Cr	8,45
	O	15	Cr	15	2 x 4 Ø	Y4	M6x12	Pg	M6x12		Ø	S1	215	Cr	215
	P1	30	Cr	30		F1	40	Cr	40		Ø	Y1	M12	Pg	M12
	P2	30	Cr	30		F2	24	Cr	24	Coppia in ingresso a vuoto					
	P3	30	Cr	30	2 x 1 Ø	Y7	10	µm	10	linea 1			1 Nm		
	P4	30	Cr	30	2 x 5 Ø	Y6	15,5	µm	15,5						
	T	14	Cr	14		Y5	24	µm	24						
	U	26	Cr	26		M H6	10 ^{+0,009 0}	Cmm	10,002				Linea	Rigidità	
2 x 1 Ø	Y3	M6x12	Pg	M6x12		⊥	m	0,05	Cmm	0,023	Rigidità torsionale (Nm/arcmin)			1	243,75
	R	186 ^{+0,2 +0,1}	Cmm	186,153	A		W	110 ^{+0,02 -0,02}	Cmm	110,02	Rigidità radiale (N/µm)			1	552
⊙	r	0,1	Cmm	0,022		//	w	0,03	/A	Cmm	0,005				

PIGNONE IN USCITA						Livello di rumore	
	J1139				@1600 rpm entrata (dB(A))	61,5	
Scostamento (su 4 denti)							
	G1	44,27 ⁰ _{-0,03}	Cmm	44,25			
	g1	0,022	Di	0,01			

Visa: P VASLIER


 1, Rue Paul De Fontenay
 F- 45210 FERRIERES
 www.redex-group.com