

KRP		Page
Scheda di prestazione	RX183-006-A	1/2
CLIENTE:	PAMA	RIF. ORDINE CLIENTE: 131 PAMA
DISTRIBUTORE:	ANDANTEX S.r.l	ORDINE INTERNO: 215788
DESIGNAZIONE:	KRP4+M.61.3.H.35/48	NUMERO DI SERIE: 905601
RIFERIMENTO:	RX128414-32	RIFERIMENTO DELLA FLANGIA MOTORE: RX128583-01

Per l'installazione, fare riferimento al manuale d'uso KRP (182/008)

OSSERVAZIONE SPECIFICA:

Le immagini dei prodotti sono a carattere puramente illustrativo.

KRP		Page
Scheda di prestazione	RX183-006-A	2/2
INTERFACCE E DIMENSIONI ESTERNE:		SN: 905601

The drawing illustrates the external dimensions and interfaces of the KRP pump assembly. The main cross-sectional view shows the following features and dimensions:

- Top Flange:** Labeled with $4 \times Y$ on PCD S , indicating four mounting holes. The outer diameter is $\varnothing B$ and the inner diameter is $\varnothing C$. The thickness of the flange is D .
- Body:** The main body has a total height of A .
- Intermediate Flange:** Labeled with $\varnothing E1$ for the outer diameter and $n \times H$ on PCD J for the mounting holes. The inner diameter is $\varnothing E2$.
- Lower Section:** The lower section has a height of L .
- Output Gear:** The gear has an outer diameter of $G1$. A detail view shows the gear profile and a keyway labeled $g1$.

General tolerance: Js13			Cmm	Automatic / manual coordinate-measuring machine			µm	Micrometer		Cr	Calliper rule		Di	Dial indicator		Pg	Plug gauge												
CASSA ESTERNA							PIGNONE IN USCITA							FLANGIA DEL MOTORE															
		richiesta				misurata				richiesta				misurata				richiesta				misurata							
						E2609								J854															
		E1		285h7 ⁰ _{-0,052}		µm		284,97		Scostamento (su 3 denti)							Ø		B		181		µm		181				
		E2		285h7 ⁰ _{-0,052}		µm		284,98				G1		46,9 ⁰ _{-0,03}		Cmm		46,885		Ø		C		38 ^{+0,05} _{+0,025}		µm		38,05	
n x H on PCD J		16 Ø14 on PCD 310		Cr		16 Ø14 on PCD 310		↗		g1		0,022		Di		0,02				D		8		Cr		8,5			
				Cr																				215					
		A		373,5		µm		374,35		Coppia in ingresso a vuoto							Ø		Y1		M12		Pg		M12				
		L		141		µm		140,84				linea 1		1 Nm															
																	Livello di rumore												
												Linea		Rigidità				@1300 rpm entrata (dB(A))		61,0									
												Rigidità torsionale (Nm/arcmin)		1		574,81													
												Rigidità radiale (N/µm)		1		1348													