

INTERFACCE E DIMENSIONI ESTERNE:		SN:	905651
---	--	------------	---------------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta			misurata		richiesta			misurata		richiesta			misurata			
			E3327													
	Y2	M6x12	Pg	M6x12		L1	60	Cr	60							
Ø	S2	165 ^{+0,1 -0,1}	Cr	165		L2	60	Cr	60		Ø	B	181	µm	181	
						J	130	Cr	130		Ø	C	38 ^{+0,05 +0,025}	µm	38,05	
	A	332	µm	332,72		K	11	Cr	11			D	8	Cr	8,5	
	E	240	Cr	240	2 x 4 Ø	Y4	M6x12	Pg	M6x12		Ø	S1	215	Cr	215	
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M12	Pg	M12	
	P1	30	Cr	30		F2	24	Cr	24	Coppia in ingresso a vuoto						
	P2	30	Cr	30	2 x 1 Ø	Y7	10	µm	10							
	P3	30	Cr	30	2 x 4 Ø	Y6	15,5	µm	15,5	linea 1			1 Nm			
	P4	30	Cr	30	2 x 5 Ø	Y5	24	µm	24	Linea					Rigidità	
	T	14	Cr	14		M H6	10 ^{+0,009 0}	Cmm	10							
	U	26	Cr	26	⊥	m	0,05	Cmm	0,022	Rigidità torsionale (Nm/arcmin)			1		243,75	
2 x 1 Ø	Y3	M6x12	Pg	M6x12		N	55 ^{+0,1 -0,1}	Cmm	54,957							
	R	186 ^{+0,2 +0,1}	Cmm	186,148	A	W	110 ^{+0,02 -0,02}	Cmm	110,01	Rigidità radiale (N/µm)			1		608	
⊙	r	0,1	Cmm	0,011	//	w	0,03	/A	Cmm							

PIGNONE IN USCITA						Livello di rumore	
	J2421				@1600 rpm entrata (dB(A))	63,0	
Scostamento (su 4 denti)							
	G1	44,27 ⁰ _{-0,03}	Cmm	44,25			
	g1	0,022	Di	0,01			

Visa: C DE MIRANDA

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com