

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	905756
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR						
requerida					real		requerida					real				
					E3330											
	Y2	M6x12	Pg	M6x12		L1	60	Cr	60							
Ø	S2	165 ^{+0,1 -0,1}	Cr	165		L2	60	Cr	60		Ø	B	131	µm	131,1	
						J	130	Cr	130		Ø	C	32 ^{+0,05 +0,025}	µm	32,03	
	A	317	µm	317,85		K	11	Cr	11			D	5	Cr	5,48	
	E	240	Cr	240	2 x 4 Ø	Y4	M6x12	Pg	M6x12		Ø	S1	165	Cr	165	
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M10	Pg	M10	
	P1	30	Cr	30		F2	24	Cr	24	Par entrada sin carga						
	P2	30	Cr	30	2 x 1 Ø	Y7	10	µm	10							
	P3	30	Cr	30	2 x 4 Ø	Y6	15,5	µm	15,5							
	P4	30	Cr	30	2 x 5 Ø	Y5	24	µm	24	Línea 1						0,7 Nm
	T	14	Cr	14		M H6	10 ^{+0,009 0}	Cmm	10				Línea	Rigidez		
2 x 1 Ø	Y3	M6x12	Pg	M6x12		⊥	m	0,05	Cmm	0,015	Rigidez torsional (Nm/arcmin)			1	243,75	
	R	186 ^{+0,2 +0,1}	Cmm	186,149	A		W	110 ^{+0,02 -0,02}	Cmm	110,012				Rigidez radial (N/µm)		
⊙	r	0,1	Cmm	0,01		//	w	0,03	/A	Cmm	0,008					

PIÑÓN DE SALIDA					Nivel sonoro	
			J2485		@1600 rpm entrada (dB(A))	61,5
Medida cordal entre 4 dientes						
		G1	44,27 ⁰ _{-0,03}	Cmm	44,245	
	↗	g1	0,022	Di	0,015	

Las imágenes del producto son meramente ilustrativas.