

|                                  |     |        |
|----------------------------------|-----|--------|
| INTERFACCE E DIMENSIONI ESTERNE: | SN: | 905798 |
|----------------------------------|-----|--------|



| CASSA ESTERNA     |    |                                     |          |                        | PIGNONE IN USCITA          |    |                                     |          |        | FLANGIA DEL MOTORE |    |                                       |          |       |
|-------------------|----|-------------------------------------|----------|------------------------|----------------------------|----|-------------------------------------|----------|--------|--------------------|----|---------------------------------------|----------|-------|
| richiesta         |    |                                     | misurata |                        | richiesta                  |    |                                     | misurata |        | richiesta          |    |                                       | misurata |       |
|                   |    |                                     | E718     |                        |                            |    |                                     | J1205    |        |                    |    |                                       |          |       |
|                   | E1 | 255h <sup>0</sup> <sub>-0,052</sub> | μm       | 254,99                 | Scostamento (su 3 denti)   |    |                                     |          |        | ∅                  | B  | 181                                   | μm       | 181   |
|                   | E2 | 255h <sup>0</sup> <sub>-0,052</sub> | μm       | 254,99                 |                            | G1 | 39,25 <sup>0</sup> <sub>-0,03</sub> | Cmm      | 39,235 | ∅                  | C  | 38 <sup>+0,05</sup> <sub>+0,025</sub> | μm       | 38,05 |
| n x H<br>on PCD J |    | 16 Ø13,5 on<br>PCD 280              | Cr       | 16 Ø13,5 on<br>PCD 280 | ↗                          | g1 | 0,022                               | Di       | 0,015  |                    | D  | 8                                     | Cr       | 8,5   |
|                   |    |                                     | Cr       | PCD 280                |                            |    |                                     |          |        | ∅                  | S1 | 215                                   | Cr       | 215   |
|                   | A  | 328,5                               | μm       | 329,3                  | Coppia in ingresso a vuoto |    |                                     |          |        | ∅                  | Y1 | M12                                   | Pg       | M12   |
|                   | L  | 121                                 | μm       | 121                    | linea 1                    |    |                                     | 1,5 Nm   |        |                    |    |                                       |          |       |

|  |                                    |              |                 |                           |      |
|--|------------------------------------|--------------|-----------------|---------------------------|------|
|  |                                    | <b>Linea</b> | <b>Rigidità</b> | @1600 rpm entrata (dB(A)) | 65,0 |
|  | Rigidità torsionale<br>(Nm/arcmin) | 1            | 473,03          |                           |      |
|  | Rigidità radiale<br>(N/μm)         | 1            | 864             |                           |      |

Visa: C DE MIRANDA

