

INTERFACCE E DIMENSIONI ESTERNE:	SN:	905906
----------------------------------	-----	--------



CASSA ESTERNA					PIGNONE IN USCITA					FLANGIA DEL MOTORE					
richiesta			misurata		richiesta			misurata		richiesta			misurata		
			E3809					J3495							
	E1	255h7 ⁰ _{-0,052}	μm	254,995	Scostamento (su 3 denti)						Ø	B	180H6 ^{+0,025} ₀	μm	180,01
	E2	255h7 ⁰ _{-0,052}	μm	254,99		G1	39,25 ⁰ _{-0,03}	Cmm	39,23		Ø	C	38F7 ^{+0,050} _{+0,025}	μm	38,05
n x H on PCD J		16 Ø13,5 on PCD 280	Cr	16 Ø13,5 on PCD 280		g1	0,022	Di	0,01			D	8	Cr	8,15
			Cr	PCD 280							Ø	S1	215	Cr	215
	A	328,5	μm	329,56	Coppia in ingresso a vuoto						Ø	Y1	M12	Pg	M12
	L	121	μm	121,01	linea 1			1,3 Nm							

		Linea	Rigidità	@1600 rpm entrata (dB(A))	69,5
	Rigidità torsionale (Nm/arcmin)	1	473,03		
	Rigidità radiale (N/μm)	1	1070		

Visa: C DE MIRANDA

