

INTERFACCE E DIMENSIONI ESTERNE:	SN:	906056
----------------------------------	-----	--------



CASSA ESTERNA						PIGNONE IN USCITA						FLANGIA DEL MOTORE					
richiesta			misurata			richiesta			misurata			richiesta			misurata		
			E3816						J3486								
	E1	255h ₀ ⁰ _{-0,052}	μm	254,98	Scostamento (su 3 denti)						∅	B	180H6 ₀ ^{+0,025}	μm	180,005		
	E2	255h ₀ ⁰ _{-0,052}	μm	254,98		G1	39,25 _{-0,03} ⁰	Cmm	39,225	∅	C	38F7 ₀ ^{+0,050} _{+0,025}	μm	38,05			
n x H on PCD J		16 Ø13,5 on PCD 280	Cr	16 Ø13,5 on PCD 280		↗	g1	0,022	Di	0,02		D	8	Cr	8,03		
			Cr								∅	S1	215	Cr	215		
	A	328,5	μm	329,34	Coppia in ingresso a vuoto						∅	Y1	M12	Pg	M12		
	L	121	μm	121	linea 1			1.2 Nm									

		Linea	Rigidità	@1600 rpm entrata (dB(A))	65,0
	Rigidità torsionale (Nm/arcmin)	1	473,03		
	Rigidità radiale (N/μm)	1	1060		

Visa: C DE MIRANDA

