

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	906233
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR										
requerida					real		requerida					real		requerida					real	
					E4101															
	Y2	M6x12	Pg	M6x12		L1	60	Cr	60		Ø	B	181	µm	181,02					
Ø	S2	165 ^{+0,1 -0,1}	Cr	165		L2	60	Cr	60		Ø	C	38 ^{+0,05 +0,025}	µm	38,03					
	A	332	µm	332		K	11	Cr	11			D	8	Cr	8,41					
	E	240	Cr	240	2 x 4 Ø	Y4	M6x12	Pg	M6x12		Ø	S1	215	Cr	215					
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M12	Pg	M12					
	P1	30	Cr	30		F2	24	Cr	24	Par entrada sin carga										
	P2	30	Cr	30	2 x 1 Ø	Y7	10	µm	10											
	P3	30	Cr	30	2 x 4 Ø	Y6	15,5	µm	15,5	Línea 1					1,8 Nm					
	P4	30	Cr	30	2 x 5 Ø	Y5	24	µm	24											
	T	14	Cr	14		M H6	10 ^{+0,009 0}	Cmm	10				Línea	Rigidez						
2 x 1 Ø	Y3	M6x12	Pg	M6x12		⊥	m	0,05	Cmm	0,025	Rigidez torsional (Nm/arcmin)			1	243,75					
	R	186 ^{+0,2 +0,1}	Cmm	186,149	A		W	110 ^{+0,1 -0,1}	Cmm	55,028										
⊙	r	0,1	Cmm	0,004		//	w	0,03	/A	Cmm	0,011	Rigidez radial (N/µm)			1	554				

PIÑÓN DE SALIDA						Nivel sonoro	
				J2664		@1600 rpm entrada (dB(A))	64,0
Medida cordal entre 4 dientes							
		G1	44,27 ⁰ _{-0,03}	Cmm		44,25	
	↗	g1	0,022	Di		0,01	

Revisado: P VASLIER



REDEX 1, Rue Paul De Fontenay
F- 45210 FERRIERES
www.redex-group.com

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com