

INTERFACCE E DIMENSIONI ESTERNE:	SN:	906622
----------------------------------	-----	--------



CASSA ESTERNA					PIGNONE IN USCITA					FLANGIA DEL MOTORE				
richiesta			misurata		richiesta			misurata		richiesta			misurata	
			E8173					H753						
	E1	255h7 ⁰ _{-0,052}	μm	254,98	Scostamento (su 3 denti)					∅	B	180H6 ^{+0,025} ₀	μm	180,02
	E2	255h7 ⁰ _{-0,052}	μm	254,98		G1	39,25 ⁰ _{-0,03}	Cmm	39,225	∅	C	38F7 ^{+0,050} _{+0,025}	μm	38,04
n x H on PCD J		16 Ø13,5 on PCD 280	Cr	16 Ø13,5 on PCD 280		g1	0,022	Di	0,01		D	8	Cr	8,03
			Cr	PCD 280						∅	S1	215	Cr	215
	A	328,5	μm	329,28	Coppia in ingresso a vuoto					∅	Y1	M12	Pg	M12
	L	121	μm	121,13	linea 1			1,4 Nm						

		Linea	Rigidità	@1600 rpm entrata (dB(A))	61,0
	Rigidità torsionale (Nm/arcmin)	1	473,03		
	Rigidità radiale (N/μm)	1	1047		

Visa: C DE MIRANDA

