

CUSTOMER: **YONG JU** CUSTOMER ORDER REF: ***RX110316T YONGJU**
 DISTRIBUTOR: **REDEX ORDER REF: 216232**
 DESIGNATION: **KRP2.R1.31.4.H** SERIAL NUMBER: **907020**
 CODE: **RX133930-12** MOTOR FLANGE CODE:

EXTERNAL DIMENSIONS & INTERFACES: SN: **907020**



For the installation, please refer to User Manual KRP (182/008)

SPECIFIC REMARKS:

General tolerance: Js13 *Cmm* Automatic / manual coordinate-measuring machine μm Micrometer *Cr* Calliper rule *Di* Dial indicator *Pg* Plug gauge

HOUSING				OUTPUT PINION				MOTOR FLANGE			
requirement		measure		requirement		measure		requirement		measure	
		E6391				F611				-	
E1	212h7 ⁰ _{-0,046} μm		211,97	Span dimension over 4 teeth				Ø	B		μm
E2	200h7 ⁰ _{-0,046} μm		199,975	G1	44,27 ⁰ _{-0,03} <i>Cmm</i>		44,255	Ø	C		μm
n x H on PCD J	12 Ø9 on PCD 233	<i>Cr</i>	12 Ø9 on PCD 233	g1	0,022	<i>Di</i>	0,01	Ø	D		<i>Cr</i>
V	289	μm	289,35	No-load input torque				Ø	S1		<i>Cr</i>
L	94	μm	93,97	Line 1		1,1 Nm		Ø	Y1		<i>Pg</i>
Ø Q1	25 ^{+0,009} _{-0,004} μm		24,996	Noise level						@1600 rpm input (dB(A))	68,0
Ø Q2	25 ^{+0,009} _{-0,004} μm		25,001			Line	Stiffness				
				Torsional stiffness (Nm/arcmin)		1	230				
				Radial stiffness (N/ μm)		1	562				

Date: **23/11/2022**

Visa: **C DE MIRANDA**

Version: **A**

Product images are for illustrative purposes only.