

CUSTOMER: **YONG JU** CUSTOMER ORDER REF: **\*RX110316T YONGJU**  
 DISTRIBUTOR: **REDEX ORDER REF: 216232**  
 DESIGNATION: **KRP2.R1.31.4.H** SERIAL NUMBER: **907021**  
 CODE: **RX133930-12** MOTOR FLANGE CODE:

EXTERNAL DIMENSIONS & INTERFACES: SN: **907021**



For the installation, please refer to User Manual KRP (182/008)

SPECIFIC REMARKS:

General tolerance: Js13 Cmm Automatic / manual coordinate-measuring machine μm Micrometer Cr Calliper rule Di Dial indicator Pg Plug gauge

HOUSING				OUTPUT PINION				MOTOR FLANGE			
requirement		measure		requirement		measure		requirement		measure	
E6384				F600				-			
E1	212h7 <sup>0</sup> <sub>-0,046</sub> μm	211,97	Span dimension over 4 teeth				∅	B	μm		
E2	200h7 <sup>0</sup> <sub>-0,046</sub> μm	199,97	G1	44,27 <sup>0</sup> <sub>-0,03</sub> Cmm	44,25	∅	C	μm			
n x H on PCD J	12 ∅9 on PCD 233 Cr	12 ∅9 on PCD 233 Cr	g1	0,022 Di	0,01	∅	D	Cr			
V	289 μm	289,34	No-load input torque				∅	S1	Cr		
L	94 μm	94,03	Line 1				∅	Y1	Pg		
∅ Q1	25 <sup>+0,009</sup> <sub>-0,004</sub> μm	24,996	Line				Stiffness		Noise level		
∅ Q2	25 <sup>+0,009</sup> <sub>-0,004</sub> μm	24,999					@1600 rpm input (dB(A))		68,0		
				Torsional stiffness (Nm/arcmin)		1	229				
				Radial stiffness (N/μm)		1	611				

Date: **25/11/2022**

Visa: **C DE MIRANDA**

Version: **A**

Product images are for illustrative purposes only.