

CUSTOMER: **KAO MING** CUSTOMER ORDER REF: ***RX112311T KAO MING**
 DISTRIBUTOR: **REDEX ORDER REF: 217870**
 DESIGNATION: **KRP2+R.21.4.H** SERIAL NUMBER: **907983**
 CODE: **RX128908-11** MOTOR FLANGE CODE:

EXTERNAL DIMENSIONS & INTERFACES: SN: **907983**



For the installation, please refer to User Manual KRP (182/008)

SPECIFIC REMARKS:

General tolerance: Js13 Cmm Automatic / manual coordinate-measuring machine μm Micrometer Cr Calliper rule Di Dial indicator Pg Plug gauge

HOUSING				OUTPUT PINION				MOTOR FLANGE			
requirement		measure		requirement		measure		requirement		measure	
		F3548				F3736				-	
E1	212h7 ⁰ _{-0,046} μm		211,98	Span dimension over 4 teeth				∅	B		μm
E2	200h7 ⁰ _{-0,046} μm		199,985	G1	44,27 ⁰ _{-0,03} Cmm		44,25	∅	C		μm
n x H on PCD J	12 ∅9 on PCD 233	Cr	12 ∅9 on PCD 233	g1	0,022	Di	0,01	∅	D		Cr
V	289	μm	289,4	No-load input torque				∅	S1		Cr
L	94	μm	93,81	Line 1		1 Nm		∅	Y1		Pg
∅ Q1	25 ^{+0,009} _{-0,004} μm		24,999	Noise level						@1600 rpm input (dB(A))	72,0
∅ Q2	25 ^{+0,009} _{-0,004} μm		25,003	Torsional stiffness (Nm/arcmin)		1	243,75				
				Radial stiffness (N/μm)		1	646				

Date: **04/10/2023**

Visa: **C DE MIRANDA**

Version: **A**

Product images are for illustrative purposes only.