

CUSTOMER: **YONG JU PREISION TECHNOLO** CUSTOMER ORDER REF: **RX112303T YONG JU**  
 DISTRIBUTOR: **REDEX ORDER REF: 217815**  
 DESIGNATION: **KRP2.R1.31.4.H** SERIAL NUMBER: **908190**  
 CODE: **RX133930-12** MOTOR FLANGE CODE:

EXTERNAL DIMENSIONS & INTERFACES: SN: **908190**



For the installation, please refer to User Manual KRP (182/008)

SPECIFIC REMARKS:

General tolerance: Js13 *Cmm* Automatic / manual coordinate-measuring machine  $\mu m$  Micrometer *Cr* Calliper rule *Di* Dial indicator *Pg* Plug gauge

HOUSING				OUTPUT PINION				MOTOR FLANGE			
requirement		measure		requirement		measure		requirement		measure	
		G1481				F4813				-	
E1	212h7 <sup>0</sup> <sub>-0,046</sub> $\mu m$		211,98	Span dimension over 4 teeth				$\emptyset$	B		$\mu m$
E2	200h7 <sup>0</sup> <sub>-0,046</sub> $\mu m$		199,99	$\nearrow$ G1	44,27 <sup>0</sup> <sub>-0,03</sub> <i>Cmm</i>		44,25	$\emptyset$	C		$\mu m$
n x H on PCD J	12 $\emptyset$ 9 on PCD 233	<i>Cr</i>	12 $\emptyset$ 9 on PCD 233	$\nearrow$ g1	0,022	<i>Di</i>	0,01	$\emptyset$	D		<i>Cr</i>
V	289	$\mu m$	289,44	No-load input torque				$\emptyset$	S1		<i>Cr</i>
L	94	$\mu m$	93,96	Line 1		1 Nm		$\emptyset$	Y1		<i>Pg</i>
$\emptyset$ Q1	25 <sup>+0,009</sup> <sub>-0,004</sub> $\mu m$		25,007	Noise level						@1600 rpm input (dB(A))	70,5
$\emptyset$ Q2	25 <sup>+0,009</sup> <sub>-0,004</sub> $\mu m$		25,008	Torsional stiffness (Nm/arcmin)		1	243,75				
				Radial stiffness (N/ $\mu m$ )		1	581				

Date: **15/12/2023**

Visa: **C DE MIRANDA**

Version: **A**

Product images are for illustrative purposes only.