

INTERFACCE E DIMENSIONI ESTERNE:	SN:	908392
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta			misurata		richiesta			misurata		richiesta			misurata			
			G4767													
	Y2	M8x15	Pg	M8x15		L1	75	Cr	75							
Ø	S2	200 ^{+0,1} _{-0,1}	Cr	200		L2	70	Cr	70		Ø	B	131	µm	131	
						J	160	Cr	160		Ø	C	32 ^{+0,05} _{+0,025}	µm	32,025	
	A	374,5	µm	374,52		K	13	Cr	13			D	5	Cr	5,51	
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	165	Cr	165	
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M10	Pg	M10	
	P1	35	Cr	35		F2	25	Cr	25	Coppia in ingresso a vuoto						
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12							
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			09 Nm			
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26	Linea					Rigidità	
	T	17	Cr	17		M H6	12 ^{+0,011} ₀	Cmm	12,009							
	U	32	Cr	32	⊥	m	0,05	Cmm	0,041	Rigidità torsionale (Nm/arcmin)			1		473,03	
2 x 1 Ø	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1} _{-0,1}	Cmm	71,507							
	R	226 ^{+0,2} _{+0,1}	Cmm	226,139	A	W	135 ^{+0,035} _{-0,035}	Cmm	135,012	Rigidità radiale (N/µm)			1		919	
⊙	r	0,1	Cmm	0,011	//	w	0,03	/A	Cmm							

PIGNONE IN USCITA						Livello di rumore	
	F5267				@1600 rpm entrata (dB(A))	69,0	
Scostamento (su 3 denti)							
	G1	39,25 ⁰ _{-0,03}	Cmm	39,234			
	g1	0,022	Di	0,01			

Visa: C DE MIRANDA

REDEX

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com