

INTERFACCE E DIMENSIONI ESTERNE:		SN:	908467
---	--	------------	---------------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE					
richiesta			misurata		richiesta			misurata		richiesta			misurata		
			G7696												
	Y2	M8x15	Pg	M8x15		L1	75	Cr	75						
Ø	S2	200 ^{+0,1} _{-0,1}	Cr	200		L2	70	Cr	70		Ø	B	131	µm 131	
	A	374,5	µm	374,48		J	160	Cr	160		Ø	C	32 ^{+0,05} _{+0,025}	µm 32,025	
	E	290	Cr	290		K	13	Cr	13			D	5	Cr 5,53	
	O	25	Cr	25	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	165	Cr 165	
	P1	35	Cr	35		F1	50	Cr	50		Ø	Y1	M10	Pg M10	
	P2	35	Cr	35		F2	25	Cr	25	Coppia in ingresso a vuoto					
	P3	35	Cr	35	2 x 1 Ø	Y7	12	µm	12						
	P4	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			1 Nm		
	T	17	Cr	17	2 x 5 Ø	Y5	26	µm	26						
	U	32	Cr	32		M H6	12 ^{+0,011} ₀	Cmm	12			Linea	Rigidità		
2 x 1 Ø	Y3	M8x15	Pg	M8x15		⊥	m	0,05	Cmm	0,008	Rigidità torsionale (Nm/arcmin)		1	473,03	
	R	226 ^{+0,2} _{+0,1}	Cmm	226,128	A		W	135 ^{+0,035} _{-0,035}	Cmm	135,018					
⊙	r	0,1	Cmm	0,016		//	w	0,03	/A	Cmm	0,011	Rigidità radiale (N/µm)		1	910

PIGNONE IN USCITA						Livello di rumore	
	F5219				@1600 rpm entrata (dB(A))	62,0	
Scostamento (su 3 denti)							
	G1	39,25 ⁰ _{-0,03}	Cmm	39,225			
	g1	0,022	Di	0,01			

Visa: P.Vaslier

REDEX 1, Rue Paul De Fontenay
F- 45210 FERRIERES
www.redex-group.com

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com