

KRP

Ficha de resultado

RX183-006-A

Page1/2

CLIENTE:

NICOLAS CORREA

REF. PEDIDO:

*110007433 NICOLAS CORREA

DISTRIBUIDOR:

PEDIDO INTERNO:

218382

DESIGNACIÓN:

KRP2.R1.31.4.H

NÚMERO DE SERIE:

908651

REFERENCIA :

RX133930-12

REFERENCIA DE LA BRIDA MOTOR:

Para la instalación, por favor consulte el Manual de Usuario KRP (182/008)

OBSERVACIONES:

Las imágenes del producto son meramente ilustrativas.

KRP

Ficha de resultado

RX183-006-A

Page2/2

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

908651

Technical drawing of the KRP2.R1.31.4.H motor assembly. The drawing includes a front view showing dimensions V, L, and ØQ1, ØQ2. A side view shows dimensions D, ØC, ØB, and 4 x Y on PCD S. A detail view shows dimensions ØE1, n x H on PCD J, and ØE2. A gear detail shows dimension G1 and a note g1.

General tolerance: Js13			Cmm	Automatic / manual coordinate-measuring machine		µm	Micrometer		Cr	Calliper rule		Di	Dial indicator		Pg	Plug gauge		
CARCASA						PIÑÓN DE SALIDA						BRIDA MOTOR						
requerida				real		requerida				real		requerida				real		
				G4694						F4925						-		
	E1	212h7 ⁰ _{-0,046}	µm	211,985		Medida cordal entre 4 dientes						Ø	B		µm			
	E2	200h7 ⁰ _{-0,046}	µm	199,985			G1	44,27 ⁰ _{-0,03}	Cmm	44,254		Ø	C		µm			
n x H on PCD J		12 Ø9 on PCD 233	Cr	12 Ø9 on PCD 233		↗	g1	0,022	Di	0,02			D		Cr			
			Cr	PCD 233								Ø	S1		Cr			
	V	289	µm	289,36		Par entrada sin carga						Ø	Y1		Pg			
	L	94	µm	93,97		Línea 1				0,8 Nm								
Ø	Q1	25 ^{+0,009} _{-0,004}	µm	24,998								Nivel sonoro						
Ø	Q2	25 ^{+0,009} _{-0,004}	µm	25,003						Línea	Rigidez		@1600 rpm entrada (dB(A))				70,0	
						Rigidez torsional (Nm/arcmin)		1	243,75									
						Rigidez radial (N/µm)		1	658									