

INTERFACCE E DIMENSIONI ESTERNE:	SN:	908760
----------------------------------	-----	--------



CASSA ESTERNA					PIGNONE IN USCITA					FLANGIA DEL MOTORE					
richiesta			misurata		richiesta			misurata		richiesta			misurata		
			G4670					F4858							
	E1	212h ⁰ _{-0,046}	μm	211,97	Scostamento (su 4 denti)					∅	B	180H6 ^{+0,025} ₀	μm	180	
	E2	200h ⁰ _{-0,046}	μm	199,97		G1	44,27 ⁰ _{-0,03}	Cmm	44,245	∅	C	38F7 ^{+0,050} _{+0,025}	μm	38,025	
n x H on PCD J		12 ∅9 on PCD 233	Cr	12 ∅9 on PCD 233		↗	g1	0,022	Di	0,01		D	8	Cr	8,03
			Cr							∅	S1	215	Cr	215	
	A	288	μm	288,84	Coppia in ingresso a vuoto					∅	Y1	M12	Pg	M12	
	L	94	μm	93,88	linea 1			0,7 Nm							

		Linea	Rigidità	@1600 rpm entrata (dB(A))	63,5
	Rigidità torsionale (Nm/arcmin)	1	243,75		
	Rigidità radiale (N/μm)	1	554		

Visa: C DE MIRANDA

