

KRP

Ficha de resultado

RX183-006-A

Page1/2

CLIENTE:

NICOLAS CORREA

REF. PEDIDO:

110009792

DISTRIBUIDOR:

PEDIDO INTERNO:

219069

DESIGNACIÓN:

KRP2.R1.31.4.H

NÚMERO DE SERIE:

908925

REFERENCIA :

RX133930-12

REFERENCIA DE LA BRIDA MOTOR:

Para la instalación, por favor consulte el Manual de Usuario KRP (182/008)

OBSERVACIONES:

Las imágenes del producto son meramente ilustrativas.

KRP

Ficha de resultado

RX183-006-A

Page2/2

INTERFACES Y DIMENSIONES EXTERIORES:

SN:

908925

Technical drawing of the KRP2.R1.31.4.H motor assembly. The drawing includes a front view, a side view, and a detail view of the output pinion. Dimensions are indicated as follows: Front view: $\phi Q1$, $\phi Q2$, $\phi E1$, $\phi E2$, $n \times H$ on PCD J, $G1$, $g1$. Side view: ϕC , ϕB , $4 \times Y$ on PCD S. Detail view: $G1$, $g1$.

General tolerance: Js13			Cmm	Automatic / manual coordinate-measuring machine		µm	Micrometer		Cr	Calliper rule		Di	Dial indicator		Pg	Plug gauge	
CARCASA						PIÑÓN DE SALIDA						BRIDA MOTOR					
requerida				real		requerida				real		requerida				real	
				G5961						F4910						-	
		E1	212h7 ⁰ _{-0,046}	µm	211,995	Medida cordal entre 4 dientes						Ø	B		µm		
		E2	200h7 ⁰ _{-0,046}	µm	199,985		G1	44,27 ⁰ _{-0,03}	Cmm	44,25	Ø	C		µm			
n x H on PCD J		12 Ø9 on PCD 233	Cr	12 Ø9 on PCD 233		↗	g1	0,022	Di	0,01		D		Cr			
			Cr							Ø	S1		Cr				
		V	289	µm	289,27	Par entrada sin carga						Ø	Y1		Pg		
		L	94	µm	93,92	Línea 1				1,2 Nm							
Ø	Q1	25	+0,009 -0,004	µm	24,998					Nivel sonoro							
Ø	Q2	25	+0,009 -0,004	µm	25,001					Línea	Rigidez	@1600 rpm entrada (dB(A))				66,5	
						Rigidez torsional (Nm/arcmin)		1	243,75								
						Rigidez radial (N/µm)		1	547								