

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	908965
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR					
requerida					real		requerida					real			
					G4203										
	Y2	M6x12	Pg	M6x12		L1	60	Cr	60						
Ø	S2	165 ^{+0,1 -0,1}	Cr	164,91		L2	60	Cr	60		Ø	B	115	µm	114,95
						J	130	Cr	130		Ø	C	35 ^{+0,05 +0,025}	µm	35,03
	A	332	µm	332,7		K	11	Cr	11			D	8	Cr	8,48
	E	240	Cr	240	2 x 4 Ø	Y4	M6x12	Pg	M6x12		Ø	S1	200	Cr	199,98
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M12	Pg	M12
	P1	30	Cr	30		F2	24	Cr	24						
	P2	30	Cr	30	2 x 1 Ø	Y7	10	µm	10	Par entrada sin carga					
	P3	30	Cr	30	2 x 4 Ø	Y6	15,5	µm	15,5	Línea 1				1,8 Nm	
	P4	30	Cr	30	2 x 5 Ø	Y5	24	µm	24						
	T	14	Cr	14		M H6	10 ^{+0,009 0}	Cmm	10				Línea	Rigidez	
2 x 1 Ø	Y3	M6x12	Pg	M6x12		⊥	m	0,05	Cmm	0,011	Rigidez torsional (Nm/arcmin)			1	243,75
	R	186 ^{+0,2 +0,1}	Cmm	186,139	A		W	110 ^{+0,02 -0,02}	Cmm	109,983	Rigidez radial (N/µm)			1	552
⊙	r	0,1	Cmm	0,009		//	w	0,03	/A	Cmm	0,001				

PIÑÓN DE SALIDA					Nivel sonoro	
			F4961		@1600 rpm entrada (dB(A))	66,5
Medida cordal entre 4 dientes						
		G1	44,27 ⁰ _{-0,03}	Cmm	44,245	
	↗	g1	0,022	Di	0,01	



Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com