

KRP

PERFORMANCE SHEET

RX183-006-A

1/2

CUSTOMER:REDEX SHANGHAI REPAIRING

CUSTOMER ORDER REF:*RXCN202404031 JIANGSU JUD

DISTRIBUTOR:REDEX SHANGHAI REPAIRING

REDEX ORDER REF:219194

DESIGNATION:KRP3.R1.31.4.H

SERIAL NUMBER:909047

CODE:RX135700-12

MOTOR FLANGE CODE:RX129474-04

Page

2/2

EXTERNAL DIMENSIONS & INTERFACES:

SN:909047

Technical drawing of the KRP3.R1.31.4.H motor showing front, side, and detail views with dimensions: Q1, Q2, V, L, E1, E2, G1, g1, D, C, B, Y, J, S.

General tolerance: Js13

Cmm

Automatic / manual coordinate-measuring machine

µm

Micrometer

Cr

Calliper rule

Di

Dial indicator

Pg

Plug gauge

HOUSING

OUTPUT PINION

MOTOR FLANGE

requirement		measure		requirement		measure		requirement		measure			
		G6254				F5255				E516			
E1	255h7 ⁰ _{-0,052} µm	254.99	Span dimension over 3 teeth				Ø	B	114,3 ^{+0,047} _{+0,012} µm	114.035			
E2	255h7 ⁰ _{-0,052} µm	254.99	Ø	G1	39,25 ⁰ _{-0,03} Cmm	39.225	Ø	C	35 ^{+0,05} _{+0,025} µm	35.025			
n x H on PCD J		16 Ø13,5 on PCD 280	Cr	16 Ø13,5 on PCD 280	g1	0,022	Di	0.01	Ø	D	8	Cr	8
V	337	µm	337.11	No-load input torque				Ø	S1	200	Cr	200	
L	121	µm	120.91	Line 1				2 Nm	Ø	Y1	M12	Pg	M12
Ø	Q1	30 ^{+0,009} _{-0,004} µm	30.001	Noise level				@1600 rpm input (dB(A))				69.5	
Ø	Q2	30 ^{+0,009} _{-0,004} µm	30.002	Torsional stiffness (Nm/arcmin)				1	473,03				
				Radial stiffness (N/µm)				1	856				

For the installation, please refer to User Manual KRP (182/008)

SPECIFIC REMARKS:

Date:26/09/2024

Visa:C DE MIRANDA

Version:A

Product images are for illustrative purposes only.

REDEX

1, Rue Paul De Fontenay
F- 45210 FERRIERES
www.redex-group.com

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com

REDEX

1, Rue Paul De Fontenay
F- 45210 FERRIERES
www.redex-group.com

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com