

INTERFACCE E DIMENSIONI ESTERNE:	SN:	909208
----------------------------------	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta			misurata		richiesta			misurata		richiesta			misurata			
			H5031					51								
	Y2	M6x12	Pg	M6x12		L2	48	Cr	48		Ø	B	131	µm	131	
Ø	S2	120 ^{+0,1 -0,1}	Cr	120		J	105	Cr	105		Ø	C	32 ^{+0,05 +0,025}	µm	32,025	
	A	253	µm	253,51		K	11	Cr	11			D	8	Cr	8,50	
	E	175	Cr	175	2 x 4 Ø	Y4	M6x12	Pg	M6x12		Ø	S1	165	Cr	165	
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M10	Pg	M10	
	P1	24	Cr	24		F2	24	Cr	24	Coppia in ingresso a vuoto						
	P2	24	Cr	24	2 x 1 Ø	Y7	10	µm	10							
	P3	24	Cr	24	2 x 4 Ø	Y6	11	µm	11	linea 1			0,2 Nm			
	P4	24	Cr	24	2 x 5 Ø	Y5	18	µm	18	Linea					Rigidità	
	T	14	Cr	14		M H6	8 ^{+0,009 0}	Cmm	8,002							
	U	26	Cr	26	⊥	m	0,05	Cmm	0,006	Rigidità torsionale (Nm/arcmin)			1		81,39	
2 x 1 Ø	Y3	M6x12	Pg	M6x12		N	47 ^{+0,1 -0,1}	Cmm	47,053							
	R	135 ^{+0,2 +0,1}	Cmm	135,128	A	W	80 ^{+0,02 -0,02}	Cmm	80,014	Rigidità radiale (N/µm)			1		338	
⊙	r	0,1	Cmm	0,018	//	w	0,03	/A	Cmm							

PIGNONE IN USCITA						Livello di rumore	
	G7182				@1600 rpm entrata (dB(A))	65,0	
Scostamento (su 3 denti)							
	G1	23,28 ⁰ _{-0,03}	Cmm	23,26			
	g1	0,021	Di	0,01			

Visa: C DE MIRANDA



Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com