

INTERFACCE E DIMENSIONI ESTERNE:		SN:	909269
----------------------------------	--	-----	--------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta			misurata		richiesta			misurata		richiesta			misurata			
			G4280													
	Y2	M8x16	Pg	M8x16		L1	81	Cr	81							
Ø	S2	234 ^{+0,1} _{-0,1}	Cr	234		L2	79	Cr	79		Ø	B	181	µm 180,82		
						J	185	Cr	185		Ø	C	38 ^{+0,05} _{+0,025}	µm 38,03		
	A	436	µm	437,18		K	15	Cr	15			D	8	Cr 8,53		
	E	320	Cr	320	2 x 4 Ø	Y4	M10x13	Pg	M10x13		Ø	S1	215	Cr 215		
	O	20	Cr	20		F1	60	Cr	60		Ø	Y1	M12	Pg M12		
	P1	40	Cr	40		F2	30	Cr	30	Coppia in ingresso a vuoto						
	P2	40	Cr	40	2 x 1 Ø	Y7	14	µm	14							
	P3	40	Cr	40	2 x 4 Ø	Y6	22	µm	22	linea 1			0,8 Nm			
	P4	40	Cr	40	2 x 5 Ø	Y5	33	µm	33	Rigidità torsionale (Nm/arcmin)					1	574,81
	T	20	Cr	20		M H6	15 ^{+0,011} ₀	Cmm	15,01							
	U	37	Cr	37	⊥	m	0,05	Cmm	0,012	Rigidità radiale (N/µm)			1	1143		
2 x 1 Ø	Y3	M10x13	Pg	M10x13		N	72,5 ^{+0,1} _{-0,1}	Cmm	72,51							
	R	255 ^{+0,2} _{+0,1}	Cmm	255,15	A	W	158 ^{+0,035} _{-0,035}	Cmm	157,998	Rigidità radiale (N/µm)					1	1143
⊙	r	0,1	Cmm	0,035	//	w	0,03	/A Cmm	0,001							

PIGNONE IN USCITA						Livello di rumore	
	G7014				@1300 rpm entrata (dB(A))	60,5	
Scostamento (su 3 denti)							
	G1	46,9 ⁰ _{-0,03}	Cmm	46,883			
	g1	0,022	Di	0,01			

Visa: C DE MIRANDA

REDEX 1, Rue Paul De Fontenay
F- 45210 FERRIERES
www.redex-group.com

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com