

ANSCHLÜSSE & AUSSENABMESSUNGEN: SN: 909319



GEHÄUSE					GEHÄUSE					MOTORFLANSCH					
Sollwert			Istwert		Sollwert			Istwert		Sollwert			Istwert		
			G9421					L1	75	Cr	75				
	Y2	M8x15	Pg	M8x15		L2	70	Cr	70		Ø	B	181	µm	181
Ø	S2	200 ^{+0,1} _{-0,1}	Cr	200		J	160	Cr	160		Ø	C	38 ^{+0,05} _{+0,025}	µm	38,03
	A	399,5	µm	399,54		K	13	Cr	13			D	8	Cr	8,51
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	215	Cr	215
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M12	Pg	M12
	P1	35	Cr	35		F2	25	Cr	25	Leerlaufdrehmoment					
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12						
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	Linie 1			0,6 Nm		
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26						
	T	17	Cr	17		M H6	12 ^{+0,011} ₀	Cmm	12,004						
	U	32	Cr	32	⊥	m	0,05	Cmm	0,015	Verdrehsteifigkeit (Nm/arcmin)		1	473,03		
2 x 1 Ø	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1} _{-0,1}	Cmm	71,518						
	R	226 ^{+0,2} _{+0,1}	Cmm	226,131	A	W	135 ^{+0,035} _{-0,035}	Cmm	135,018	Radiale Steifigkeit (N/µm)		1	1184		
⊙	r	0,1	Cmm	0,004	//	w	0,03	/A	Cmm						0,013

ABTRIEBSRITZEL					Geräuschpegel	
			G7107		@1600 rpm Eintrieb (dB(A))	64,0
Zahnweite (über 3 Zähne)						
		G1	39,25 ⁰ _{-0,03}	Cmm	39,225	
	↗	g1	0,022	Di	0,01	

Von: P. Vaslier



Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com