

INTERFACCE E DIMENSIONI ESTERNE:		SN:	909440
---	--	------------	---------------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE					
richiesta			misurata		richiesta			misurata		richiesta			misurata		
			G6602												
	Y2	M6x12	Pg	M6x12		L1	60	Cr	60						
Ø	S2	165 ^{+0,1 -0,1}	Cr	165		L2	60	Cr	60		Ø	B	181 ^{+0,05 +0,025}	µm	181
	A	332	µm	332.63		J	130	Cr	130		Ø	C	38	µm	38.025
	E	240	Cr	240		K	11	Cr	11			D	8	Cr	8.49
	O	15	Cr	15	2 x 4 Ø	Y4	M6x12	Pg	M6x12		Ø	S1	215	Cr	215
	P1	30	Cr	30		F1	40	Cr	40		Ø	Y1	M12	Pg	M12
	P2	30	Cr	30		F2	24	Cr	24	Coppia in ingresso a vuoto					
	P3	30	Cr	30	2 x 1 Ø	Y7	10	µm	10						
	P4	30	Cr	30	2 x 4 Ø	Y6	15,5	µm	15,5	linea 1			0,9 Nm		
	T	14	Cr	14	2 x 5 Ø	Y5	24	µm	24						
	U	26	Cr	26		M H6	10 ^{+0,009 0}	Cmm	10.004			Linea	Rigidità		
2 x 1 Ø	Y3	M6x12	Pg	M6x12		m	0,05	Cmm	0.01	Rigidità torsionale (Nm/arcmin)		1	243,75		
	R	186 ^{+0,2 +0,1}	Cmm	186.152	A	W	110 ^{+0,1 -0,1}	Cmm	55.04						
⊙	r	0,1	Cmm	0.03		w	0,03	/A Cmm	0.003	Rigidità radiale (N/µm)		1	551		

PIGNONE IN USCITA						Livello di rumore	
	J281				@1600 rpm entrata (dB(A))	64.0	
Scostamento (su 4 denti)							
	G1	44,27 ⁰ _{-0,03}	Cmm	44.254			
	g1	0,022	Di	0.01			



REDEX 1, Rue Paul De Fontenay
F- 45210 FERRIERES
www.redex-group.com

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com