

|                                  |     |        |
|----------------------------------|-----|--------|
| INTERFACCE E DIMENSIONI ESTERNE: | SN: | 909606 |
|----------------------------------|-----|--------|



| CASSA ESTERNA     |    |                                     |          |                     | PIGNONE IN USCITA          |         |                                     |          |        | FLANGIA DEL MOTORE |    |                                          |          |        |
|-------------------|----|-------------------------------------|----------|---------------------|----------------------------|---------|-------------------------------------|----------|--------|--------------------|----|------------------------------------------|----------|--------|
| richiesta         |    |                                     | misurata |                     | richiesta                  |         |                                     | misurata |        | richiesta          |    |                                          | misurata |        |
|                   |    |                                     | H6471    |                     |                            |         |                                     | H4756    |        |                    |    |                                          |          |        |
|                   | E1 | 212h <sup>0</sup> <sub>-0,046</sub> | μm       | 211.98              | Scostamento (su 4 denti)   |         |                                     |          |        | ∅                  | B  | 180H6 <sup>+0,025</sup> <sub>0</sub>     | μm       | 180.01 |
|                   | E2 | 200h <sup>0</sup> <sub>-0,046</sub> | μm       | 199.975             |                            | G1      | 44,27 <sup>0</sup> <sub>-0,03</sub> | Cmm      | 44.249 | ∅                  | C  | 38F7 <sup>+0,050</sup> <sub>+0,025</sub> | μm       | 38.04  |
| n x H<br>on PCD J |    | 12 ∅9 on<br>PCD 233                 | Cr       | 12 ∅9 on<br>PCD 233 |                            | ↗<br>g1 | 0,022                               | Di       | 0.01   |                    | D  | 8                                        | Cr       | 8.03   |
|                   |    |                                     | Cr       |                     |                            |         |                                     |          |        | ∅                  | S1 | 215                                      | Cr       | 215    |
|                   | A  | 288                                 | μm       | 288.79              | Coppia in ingresso a vuoto |         |                                     |          |        | ∅                  | Y1 | M12                                      | Pg       | M12    |
|                   | L  | 94                                  | μm       | 93.85               | linea 1                    |         |                                     | 1,1 Nm   |        |                    |    |                                          |          |        |

|  |                                    | Linea | Rigidità |
|--|------------------------------------|-------|----------|
|  | Rigidità torsionale<br>(Nm/arcmin) | 1     | 243,75   |
|  | Rigidità radiale<br>(N/μm)         | 1     | 553      |

Visa: C DE MIRANDA 