

|                                  |     |        |
|----------------------------------|-----|--------|
| INTERFACCE E DIMENSIONI ESTERNE: | SN: | 909704 |
|----------------------------------|-----|--------|



| CASSA ESTERNA     |    |                                     |          |                     | PIGNONE IN USCITA                                                                     |    |                                     |          |       | FLANGIA DEL MOTORE |    |                                       |          |        |
|-------------------|----|-------------------------------------|----------|---------------------|---------------------------------------------------------------------------------------|----|-------------------------------------|----------|-------|--------------------|----|---------------------------------------|----------|--------|
| richiesta         |    |                                     | misurata |                     | richiesta                                                                             |    |                                     | misurata |       | richiesta          |    |                                       | misurata |        |
|                   |    |                                     | H6469    |                     |                                                                                       |    |                                     | J746     |       |                    |    |                                       |          |        |
|                   | E1 | 212h <sup>0</sup> <sub>-0,046</sub> | μm       | 211.97              | Scostamento (su 4 denti)                                                              |    |                                     |          |       | ∅                  | B  | 181                                   | μm       | 181    |
|                   | E2 | 200h <sup>0</sup> <sub>-0,046</sub> | μm       | 199.995             |                                                                                       | G1 | 44,27 <sup>0</sup> <sub>-0,03</sub> | Cmm      | 44.25 | ∅                  | C  | 38 <sup>+0,05</sup> <sub>+0,025</sub> | μm       | 38.035 |
| n x H<br>on PCD J |    | 12 ∅9 on<br>PCD 233                 | Cr       | 12 ∅9 on<br>PCD 233 |  | g1 | 0,022                               | Di       | 0.01  |                    | D  | 8                                     | Cr       | 8.5    |
|                   |    |                                     | Cr       |                     |                                                                                       |    |                                     |          |       | ∅                  | S1 | 215                                   | Cr       | 215    |
|                   | A  | 288                                 | μm       | 288.78              | Coppia in ingresso a vuoto                                                            |    |                                     |          |       | ∅                  | Y1 | M12                                   | Pg       | M12    |
|                   | L  | 94                                  | μm       | 93.81               | linea 1                                                                               |    |                                     | 1 Nm     |       |                    |    |                                       |          |        |

|  |                                    | Linea | Rigidità |
|--|------------------------------------|-------|----------|
|  | Rigidità torsionale<br>(Nm/arcmin) | 1     | 243,75   |
|  | Rigidità radiale<br>(N/μm)         | 1     | 634      |

Visa: C DE MIRANDA

