

KRPX			Page
Performance sheet		RX183-007-D	1/2
CUSTOMER:	ELECTROIMPACT	CUSTOMER ORDER REF:	*125706 ELECTROIMPACT
DISTRIBUTOR:		REDEX ORDER REF:	219911
DESIGNATION:	KRPX3+M.46.3.H.28/38	SERIAL NUMBER:	909740
CODE:	RX131507-13	MOTOR FLANGE CODE:	RX128581-06

For the installation, please refer to User Manual KRPX (182/010)

SPECIFIC REMARKS:

Product images are for illustrative purposes only.

KRPX			Page
Performance sheet		RX183-007-D	2/2
EXTERNAL DIMENSIONS & INTERFACES:		SN:	909740
			

General tolerance: Js13	Cmm	Automatic / manual coordinate-measuring machine	µm	Micrometer	Cr	Calliper rule	Di	Dial indicator	Pg	Plug gauge
-------------------------	-----	--	----	------------	----	---------------	----	----------------	----	------------

HOUSING					HOUSING					MOTOR FLANGE					
requirement			measure		requirement			measure		requirement			measure		
			H6844												
	Y2	M8x15	Pg	M8x15		L2	70	Cr	70		Ø	B	181	µm	181
Ø	S2	200 ^{+0,1} _{-0,1}	Cr	200		J	160	Cr	160		Ø	C	38 ^{+0,05} _{+0,025}	µm	38.025
	A	399.5	µm	399.31		K	13	Cr	13			D	8	Cr	8.51
	E	290	Cr	290	2 x 4Ø	Y4	M8x15	Pg	M8x15		Ø	S1	215	Cr	215
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M12	Pg	M12
	P1	35	Cr	35		F2	25	Cr	25						
	P2	35	Cr	35	2 x 1Ø	Y7	12	µm	12	No-load input torque					
	P3	35	Cr	35	2 x 4Ø	Y6	17,5	µm	17,5	Line 1			1,4 Nm		
	P4	35	Cr	35	2 x 5Ø	Y5	26	µm	26						
	T	17	Cr	17		M H6	12 ^{+0,011} ₀	Cmm	12.003			Line	Stiffness		
	U	32	Cr	32	⊥	m	0,05	Cmm	0.012	Torsional stiffness (Nm/arcmin)		1	473,03		
2 x 1Ø	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1} _{-0,1}	Cmm	71.505	Radial stiffness (N/µm)		1	1038		
	R	226 ^{+0,2} _{+0,1}	Cmm	226.152	A		W	135 ^{+0,035} _{-0,035}	Cmm	135.013					
⊙	r	0,1	Cmm	0.015		//	w	0,03 /A	Cmm	0.001					

OUTPUT PINION				Noise level	
G7055				@1600 rpm input (dB(A))	62.0
Span dimension over 3 teeth					
	G1	39,25	⁰ _{-0,03}	Cmm	39.23
↗	g1	0,022		Di	0.02

Date: 16/07/2025 Visa: C DE MIRANDA

Version: A