


INTERFACCE E DIMENSIONI ESTERNE:		SN:	909836
---	--	------------	---------------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta				misurata		richiesta				misurata		richiesta			misurata	
				G7712												
	Y2	M8x15	Pg	M8x15		L1	75	Cr	75			Ø	B	115	µm	115
Ø	S2	200 ^{+0,1 -0,1}	Cr	200		J	160	Cr	160		Ø	C	35 ^{+0,05 +0,025}	µm	35.045	
	A	389.5	µm	389.72		K	13	Cr	13			D	8	Cr	8.51	
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	200	Cr	200	
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M12	Pg	M12	
	P1	35	Cr	35		F2	25	Cr	25	Coppia in ingresso a vuoto						
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12							
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			1,3 Nm			
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26							
	T	17	Cr	17		M H6	12 ^{+0,011 0}	Cmm	12							
	U	32	Cr	32	⊥	m	0,05	Cmm	0.014	Rigidità torsionale (Nm/arcmin)		1	473,03			
2 x 1 Ø	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1 -0,1}	Cmm	71.52							
	R	226 ^{+0,2 +0,1}	Cmm	226.146	A	W	135 ^{+0,035 -0,035}	Cmm	135.013	Rigidità radiale (N/µm)		1	1170			
⊙	r	0,1	Cmm	0.047	//	w	0,03 /A	Cmm	0.001							

PIGNONE IN USCITA						Livello di rumore		
					G7067	@1600 rpm entrata (dB(A))	60.5	
Scostamento (su 3 denti)								
		G1	39,25 ⁰ _{-0,03}	Cmm	39.233			
		g1	0,022	Di	0.02			

Le immagini dei prodotti sono a carattere puramente illustrativo.