

INTERFACCE E DIMENSIONI ESTERNE:		SN:	910072
---	--	------------	---------------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE					
richiesta			misurata		richiesta			misurata		richiesta			misurata		
			H6817					L1 60 Cr 60							
	Y2	M6x12	Pg	M6x12		L2	60	Cr	60		Ø	B	181	µm	181,03
Ø	S2	165 ^{+0,1} _{-0,1}	Cr	165		J	130	Cr	130		Ø	C	38 ^{+0,05} _{+0,025}	µm	38,03
	A	332	µm	332,71		K	11	Cr	11			D	8	Cr	8,50
	E	240	Cr	240	2 x 4 Ø	Y4	M6x12	Pg	M6x12		Ø	S1	215	Cr	215
	O	15	Cr	15		F1	40	Cr	40		Ø	Y1	M12	Pg	M12
	P1	30	Cr	30		F2	24	Cr	24	Coppia in ingresso a vuoto					
	P2	30	Cr	30	2 x 1 Ø	Y7	10	µm	10						
	P3	30	Cr	30	2 x 4 Ø	Y6	15,5	µm	15,5	linea 1			1,6 Nm		
	P4	30	Cr	30	2 x 5 Ø	Y5	24	µm	24						
	T	14	Cr	14		M H6	10 ^{+0,009} ₀	Cmm	10,004			Linea	Rigidità		
	U	26	Cr	26	⊥	m	0,05	Cmm	0,008	Rigidità torsionale (Nm/arcmin)		1	243,75		
2 x 1 Ø	Y3	M6x12	Pg	M6x12		N	55 ^{+0,1} _{-0,1}	Cmm	55,009						
	R	186 ^{+0,2} _{+0,1}	Cmm	186,136	A	W	110 ^{+0,02} _{-0,02}	Cmm	109,994	Rigidità radiale (N/µm)		1	562		
⊙	r	0,1	Cmm	0,016	//	w	0,03	/A	Cmm						0,005

PIGNONE IN USCITA						Livello di rumore	
					J294	@1600 rpm entrata (dB(A))	63,5
Scostamento (su 4 denti)							
		G1	44,27 ⁰ _{-0,03}	Cmm	44,252		
	↗	g1	0,022	Di	0,01		

Visa: P.Vaslier



REDEX 1, Rue Paul De Fontenay
F- 45210 FERRIERES
www.redex-group.com

Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com