


INTERFACCE E DIMENSIONI ESTERNE:		SN:	910177
---	--	------------	---------------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta				misurata		richiesta				misurata		richiesta			misurata	
				J2624			L1	75	Cr	75						
	Y2	M8x15	Pg	M8x15		L2	70	Cr	70		Ø	B	180H6 ₀ ^{+0,025}	µm	180.01	
Ø	S2	200 ^{+0,1} _{-0,1}	Cr	200		J	160	Cr	160		Ø	C	38F7 ^{+0,050} _{+0,025}	µm	38.045	
	A	389.5	µm	389.63		K	13	Cr	13			D	8	Cr	8.03	
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	215	Cr	215	
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M12	Pg	M12	
	P1	35	Cr	35		F2	25	Cr	25	Coppia in ingresso a vuoto						
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12							
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			1,7 Nm			
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26							
	T	17	Cr	17		M H6	12 ^{+0,011} ₀	Cmm	12.002			Linea	Rigidità			
	U	32	Cr	32	⊥	m	0,05	Cmm	0.012	Rigidità torsionale (Nm/arcmin)		1	473,03			
2 x 1 Ø	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1} _{-0,1}	Cmm	71.483							
	R	226 ^{+0,2} _{+0,1}	Cmm	226.147	A	W	135 ^{+0,035} _{-0,035}	Cmm	135.01	Rigidità radiale (N/µm)		1	963			
⊙	r	0,1	Cmm	0.012	//	w	0,03 /A	Cmm	0.001							

PIGNONE IN USCITA						Livello di rumore	
	H5219				@1600 rpm entrata (dB(A))	60.5	
Scostamento (su 3 denti)							
	G1	39,25 ⁰ _{-0,03}	Cmm	39.23			
	g1	0,022	Di	0.01			




1, Rue Paul De Fontenay
F- 45210 FERRIERES
www.redex-group.com
Tel: +33 2 38 94 42 00
Fax: +33 2 38 94 42 99
Email: info@redex-group.com