

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	910215
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR					
requerida			real		requerida			real		requerida			real		
			J2544			L1	81	Cr	81				J3438		
Ø	Y2	M8x16	Pg	M8x16		L2	79	Cr	79	Ø	B	114,3 ^{+0,047 +0,012}	µm	114.315	
	S2	234 ^{+0,1 -0,1}	Cr	234		J	185	Cr	185	Ø	C	35 ^{+0,05 +0,025}	µm	35.025	
	V	477	µm	477.22		K	15	Cr	15		D	18	Cr	18	
	E	320	Cr	320	2 x 4Ø	Y4	M10x13	Pg	M10x13	Ø	S1	200	Cr	200	
	O	20	Cr	20		F1	60	Cr	60	Ø	Y1	M12	Pg	M12	
	P1	40	Cr	40		F2	30	Cr	30						
	P2	40	Cr	40	2 x 1Ø	Y7	14	µm	14	Par entrada sin carga					
	P3	40	Cr	40	2 x 4Ø	Y6	22	µm	22	Línea 1			3 Nm		
	P4	40	Cr	40	2 x 5Ø	Y5	33	µm	33						
	T	20	Cr	20		M H6	15 ^{+0,011 0}	Cmm	15				Línea	Rigidez	
2 x 1Ø	Y3	M10x13	Pg	M10x13		m	0,05	Cmm	0.012	Rigidez torsional (Nm/arcmin)			1	574,81	
	R	255 ^{+0,2 +0,1}	Cmm	255.12	A	N	72,5 ^{+0,1 -0,1}	Cmm	72.441						
⊙	r	0,1	Cmm	0.024	//	W	158 ^{+0,035 -0,035}	Cmm	157.992	Rigidez radial (N/µm)			1	1236	
Ø	Q1	35 ^{+0,011 -0,005}	µm	34.997		w	0,03 /A	Cmm	0.002						
PIÑÓN DE SALIDA										Nivel sonoro					
J1			/O	Di	0.02	J2382			@1300 rpm entrada (dB(A))			64.0			
Medida cordal entre 3 dientes															
		G1	46,9 ^{0 -0,03}	Cmm	46.89										
	↗	g1	0,022	Di	0.01										

Fecha: 12/01/2026

Revisado: C DE MIRANDA

Versión: A