

INTERFACCE E DIMENSIONI ESTERNE:		SN:	910478
---	--	------------	---------------



CASSA ESTERNA					CASSA ESTERNA					FLANGIA DEL MOTORE						
richiesta			misurata		richiesta			misurata		richiesta			misurata			
			J5551													
	Y2	M8x15	Pg	M8x15		L1	75	Cr	75							
	Ø	S2	200 ^{+0,1 -0,1}	Cr	200		L2	70	Cr	70		Ø	B	180H6 ^{+0,025 0}	µm	180.025
						J	160	Cr	160		Ø	C	38F7 ^{+0,050 +0,025}	µm	38.04	
	A	389.5	µm	389.65		K	13	Cr	13			D	8	Cr	8	
	E	290	Cr	290	2 x 4 Ø	Y4	M8x15	Pg	M8x15		Ø	S1	215	Cr	215	
	O	25	Cr	25		F1	50	Cr	50		Ø	Y1	M12	Pg	M12	
	P1	35	Cr	35		F2	25	Cr	25	Coppia in ingresso a vuoto						
	P2	35	Cr	35	2 x 1 Ø	Y7	12	µm	12							
	P3	35	Cr	35	2 x 4 Ø	Y6	17,5	µm	17,5	linea 1			1,3 Nm			
	P4	35	Cr	35	2 x 5 Ø	Y5	26	µm	26							
	T	17	Cr	17		M H6	12 ^{+0,011 0}	Cmm	12.003							
	U	32	Cr	32	⊥	m	0,05	Cmm	0.02	Rigidità torsionale (Nm/arcmin)		1	473,03			
2 x 1 Ø	Y3	M8x15	Pg	M8x15		N	71,5 ^{+0,1 -0,1}	Cmm	71.421							
	R	226 ^{+0,2 +0,1}	Cmm	226.148	A	W	135 ^{+0,035 -0,035}	Cmm	135.009	Rigidità radiale (N/µm)		1	1006			
⊙	r	0,1	Cmm	0.011	//	w	0,03	/A	Cmm						0.011	

PIGNONE IN USCITA						Livello di rumore	
				J1230		@1600 rpm entrata (dB(A))	62.5
Scostamento (su 3 denti)							
		G1	39,25 ⁰ _{-0,03}	Cmm	39.24		
	↗	g1	0,022	Di	0.01		

Le immagini dei prodotti sono a carattere puramente illustrativo.