

INTERFACES Y DIMENSIONES EXTERIORES:	SN:	910678
--------------------------------------	-----	--------



CARCASA					CARCASA					BRIDA MOTOR						
requerida			real		requerida			real		requerida			real			
			J2547					L1 81 Cr 81					H2120			
Ø	Y2	M8x16	Pg	M8x16		L2	79	Cr	79	Ø	B	114,3 ^{+0,047 +0,012}	µm	114,33		
	S2	234 ^{+0,1 -0,1}	Cr	234,01		J	185	Cr	185	Ø	C	35 ^{+0,05 +0,025}	µm	35,03		
	V	477	µm	477,16		K	15	Cr	15		D	18	Cr	18,33		
	E	320	Cr	320	2 x 4Ø	Y4	M10x13	Pg	M10x13	Ø	S1	200	Cr	200,03		
	O	20	Cr	20		F1	60	Cr	60	Ø	Y1	M12	Pg	M12		
	P1	40	Cr	40		F2	30	Cr	30	Par entrada sin carga						
	P2	40	Cr	40	2 x 1Ø	Y7	14	µm	14							
	P3	40	Cr	40	2 x 4Ø	Y6	22	µm	22	Línea 1			2 Nm			
	P4	40	Cr	40	2 x 5Ø	Y5	33	µm	33	Rígedez torsional (Nm/arcmin)					1	574,81
	T	20	Cr	20		M H6	15 ^{+0,011 0}	Cmm	15							
	U	37	Cr	37	⊥	m	0,05	Cmm	0,018	Rígedez radial (N/µm)			1	1409 ⁽¹⁾		
2 x 1Ø	Y3	M10x13	Pg	M10x13		N	72,5 ^{+0,1 -0,1}	Cmm	72,468							
	R	255 ^{+0,2 +0,1}	Cmm	255,122	A	W	158 ^{+0,035 -0,035}	Cmm	157,986	Nivel sonoro						
⊙	r	0,1	Cmm	0,01	//	w	0,03	/A Cmm	0,005							
Ø	Q1	35 ^{+0,011 -0,005}	µm	34,989 ⁽²⁾	PIÑÓN DE SALIDA					@1300 rpm entrada (dB(A))					64,0	
Ø	Q2	35 ^{+0,011 -0,005}	µm	35,001												
	J1	/0	Di	0	Medida cordal entre 3 dientes											
						G1	46,9 ^{0 -0,03}	Cmm	46,88							
						g1	0,022	Di	0,02							

Fecha: 23/07/2026

Revisado: C DE MIRANDA

Versión: A